

ELI-QUIP-VD4-28R: Specifications


4mp IP Vandal-proof Dome Weatherproof with IR 2.8MM



Key Features:

- 4 Mega Pixel (2560 x 1440)
- H.265 video encoding
- IP66 & IK10 ingress protection
- ICR auto switch, true day / night
- 30 ~ 65 feet IR night view distance
- 3D DNR, digital WDR
- ROI coding
- Supports local CVBS video output and one-way audio
- Supports PoE power supply
- Supports smart phone, iPad, remote monitoring
- Supports three streams

Dimensions:



Compatible Camera Mounts:

Part Number: JB-SB-UNIR



Specification Subject to change without Notice*

eLineTechnology.com

800.683.6835 | sales@el-usa.com

Become a Business Partner ask us how?

Model#: ELI-QUIP-VD4-28R	
Camera	
Image Sensor	1 / 3 "CMOS
Image Size	2688 × 1520
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed
Min. Illumination	0.05 lux @F1.2, AGC ON; 0 lux with IR
Lens	2.8 mm @F1.6, angle of view: 100°
Lens Mount	M12
Day & Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defogging	Yes
Digital NR	2D / 3D DNR
Angle Adjustment	Pan : 0°~240°, Tilt : 0°~68°, Rotation : 0°~220°
Image	
Video Compression	H.265/ H.264 / MJPEG
H.265 Compression Standard	Main Profile @Leve4.1 High Tier
Resolution	4MP (2560×1440), 3MP (2304×1296),1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
Main stream	60Hz : (1 ~ 30fps) / 1080P(1 ~ 30fps) / 720P(1 ~ 30fps) 4MP 4MP 3MP(1 ~ 30fps) / 50Hz : (1 ~ 25fps) / 3MP(1 ~ 25fps) / 1080P(1 ~ 25fps) / 720P(1 ~ 25fps)
Bit rate	64 Kbps ~ 10 Mbps
Encode Mode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. Adjustable through client software or web browser
Audio Compression	G711A / U
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Audio	One-way audio (MIC IN × 1)
Video Output	CVBS video output (BNC × 1)
Functions	
Remote Monitoring	IE browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Protocol	TCP / IP, UDP, DHCP, NTP, R Protocol TSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network remote storage
Smart Alarm	Motion Alarm
PoE	Yes
IR Distance	30-65ft (10~20m)
Water-proof	IP66