


4MP Covert IP Pin Hole Camera ELI-IP5-CV4-PIN

Key Features:

- 4MP resolution (2688 x 1520)
- 2.8mm Wide Angle Lens
- Easy to Hide Design
- No IR
- Operating Temperature -22° F ~ +140°F Less than 95% RH12vDC/PoE
- Power Supply DC12V POE (802.3af)

*Specifications are subject to change without Notice.



4MP Covert IP Pin Hole Camera

ELI-IP5-CV4-PIN

ELI-IP5-CV4-PINSU (Lens specs)				
CAMERA				
Image Sensor	1/2.7" 4Megapixel progressive scan CMOS			
Scanning System	Progressive			
Effective Pixels	2688(H)x1520(V)			
Minimum Illumination	0.02Lux/F2.4 (Color,1/3s,30IRE) 0.08Lux/F2.4 (Color,1/30s,30IRE) 0.01Lux/F2.4 (B/W,1/3s,30IRE) 0.04Lux/F2.4 (B/W,1/30s,30IRE)			
IR Distance	N/A			
IR On/Off Control	N/A			
IR LEDs	N/A			
Lens				
Lens Type	Fixed			
Mount Type	Board-in			
Focal Length	2.8mm			
Max. Aperture	F2.4			
Angle of View	H:83.4° ,V:44.9°			
Optical Zoom	N/A			
Focus Control	Fixed			
Close Focus Distance	N/A			
DORI Distance	Detect	Observe	Recognize	Identify
	61m(200ft) 2	24m(80ft)	12m(40ft)	6m(20ft)
Pan/Tilt/Rotation				
Pan/Tilt/Rotation Range	N/A			
Certifications				
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B			
Environmental				
Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH			
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH			
Ingress Protection	N/A			
Vandal Resistance	N/A			
Construction				
Casing	Metal			
Dimensions	Φ30.5mm×48.65mm(Φ1.20"×1.91")			
Net Weight	0.40Kg (0.88lb)			
Gross Weight	0.47Kg (1.03lb)			

ELI-IP5-CV4-PINMU (Modular)	
CAMERA	
RAM/ROM	512MB/32MB
S/N Ratio	More than 50dB
Intelligence	
IVS	Tripwire, Intrusion, Object Abandoned/Missing
Advanced Intelligent Functions	Face Detection
Video (working together with lens unit)	
Compression	H.265+/H.265/H.264+/H.264
Streaming Capability	3 Streams
Resolution	4M(2688×1520) / 3M(2304×1296) / 1080P(1920×1080) / 1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480) / VGA(640×480) / CIF(352×288/342×240)
Frame Rate	Main Stream: 4M (1~25/30fps) Sub Stream: D1 (1 ~ 25/30fps) Third Stream: 720P (1~25/30fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 24Kbps~ 10240Kbps H.265: 14Kbps~ 9984Kbps
Day/Night	Electronic
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detetion	Off / On (4 Zones, Rectangle)
Region of Interest	Off / On (4 Zones)
Electronic Image Stabilization (EIS)	N/A
Smart IR	N/A
Defog	N/A
Digital Zoom	16x
Flip	0°/90°/180°/270°
Mirror	Off / On
Privacy Masking	Off / On (4 Areas, Rectangle)
Audio	
Compression	G.711a/ G.711Mu/ AAC/ G.726
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP;HTTPs;TCP;ARP;RTSP;RTP;UDP;SMTP;FTP; DHCP;DNS;DDNS;PPPOE;IPv4/v6;QoS;UPnP;NTP; Bonjour;802.1x;Multicast;ICMP;IGMP;SNMP
Interoperability	ONVIF, PSIA, CGI
Streaming Method	Unicast / Multicast
Max. User Access	10 Users/20 Users
Edge Storage	NAS Local PC for instant recording Mirco SD card 128GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, Easy4ip
Smart Phone	IOS, Android

4MP Covert IP Pin Hole Camera

ELI-IP5-CV4-PIN

ELI-IP5-CV4-PINMU (Modular)	
Certifications	
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B
Interface	
Video Interface	N/A
Audio Interface	1/1 channel In/Out
RS232	1 port
Alarm	2 channel In: 5mA 5VDC 2 channel Out: 1A 30VDC / 0.5A 50VAC
Electrical	
Power Supply	DC12V, PoE(802.3af)(Class 0)
Power Consumption	<6W (working together with lens unit)
Environmental	
Operating Conditions	30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	N/A
Vandal Resistance	N/A
Construction	
Casing	Metal
Dimensions	110.0mm×82.7mm×24.0mm (4.33"×3.26"×0.95")
Net Weight	0.21Kg (0.46lb)
Gross Weight	0.30Kg (0.66lb)