

IP Bracket PTZ 2MP/1080p with 12X Zoom

ELI-IP5-PTZ21-12X

Key Features:

- 2MP/1080p Resolution
- Weatherproof IP66
- 12x Optical Zoom, 16x Digital Zoom
- Auto Focus
- WDR
- Onvif



Model No.	ELI-IP5-PTZ21-12X
Sensor	1/3" 2MP Sony Exmor CMOS
Module Type	5.1mm - 31.2mm / 12X Optical Zoom
Effect Pixels	2MP 1920x1080
Minimum Illumination	0.05 LUX Color, 0.005 LUX B&W
Lens Focal Length	51.1mm - 61.2mm / Angle of View : 51.3° - 4.64°
Day Night	Auto (ICR) / Color / B&W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto / ATW / Indoor / Outdoor / Manual
Gain Control	Auto / Manual
Noise Reduction	2D / 3D

Model No.	ELI-IP5-PTZ21-12X
Privacy Masking	Up to 24 Areas
Digital Zoom	16x
Focus Control	Auto / Manual
Resolution	1080p / 720p / D1 / CIF
Bit Rate	448K - 8192Kbps
Video Compression	H.264 / MJPEG4
Audio Compression	G.711a / G.711u (32Kbps) / PCM (128Kbps)
Audio Interface	1/1 In/Out
Ethernet	RJ45 (10/100 Base-T)
Power Over Ethernet	POE+ (802.3at)
Pan /Tilt Range	Pan: 0° - 360° Endless; Tilt -2°-90° Auto-Flip 180°
Manual Control Speed	Pan: 0.1°-300°/s Tilt: 0.1°-120°/s
Preset Speed	Pan: 300° Tilt: 200°/s
Preset	80 (DH-SD), 255 (Pelco P/D)
PTZ Mode	5 Pattern, 8 Tour, 5 Auto Scan, Auto Pan
Power up Action	Auto restore previous PTZ and Lens Status after power
Power up Action	Auto restore previous PTZ and Lens Status after power
Idle Motion	Activate Preset / Pan / Scan / Tour / Pattern
Time Task	Auto activation of Preset/Pan/Scan/Tour/Pattern
3D Positioning	Yes
Protocol	DH-SD, Pelco-P, Pelco-D (Auto Recognition)
Ethernet	RJ-45 (10/100 Base-T), POE+(802.3at)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP
ONVIF	ONVIF 2.0
Power Requirements	24VAC / 1.5A
Power Consumption	12W, 22W (Heater On)
Operating Temperature	-40° F to 140° F
PTZ Dimensions	160(mm) x 132(mm)
Weight	3lbs