

4 Channel Compact 1U POE NVR ELI-IP5-NVR4M-P

Key Features: ELI-IP5-NVR4M-P

- H.264+/H.264 codec decoding
- Max 80Mbps incoming bandwidth
- Up to 6Mp resolution preview & playback
- HDMI/VGA simultaneous video output
- Support IPC UPnP, 4PoE ports
- 3D intelligent positioning with PTZ camera
- Remote monitoring with web viewer and Mobile devices

*Specifications are subject to change without Notice.



4 Channel Compact 1U POE NVR

ELI-IP5-NVR4M-P

Model Number	ELI-IP5-NVR4M-P
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Audio Video	
IP Camera Input	4 channel
Two-way Talk	1channel Input, 1channel Output, RCA
Display	
Interface	1 HDMI,1 VGA
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/4
OSD	Camera title, Time, Camera lock, Motion detection, Recording
Recording	
Compression	H.264+/H.264
Resolution	6Mp/5Mp/4Mp/3Mp/1080P/ 720P/ D1&etc.
Record Rate	80Mbps
Bit Rate	16Kbps ~ 20Mbps Per Channel
Record Mode	Manual, Schedule(Regular(Continuous), MD, Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection and Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22× 18), Video Loss & tampering
Third-party Support	
Third-party Support	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, and more

ELI-IP5-NVR4M-P	
Playback and Backup	
Sync Playback	1/4
Search Mode	Time /Date, MD and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network/
Network	
Interface	1 RJ-45 port (10/100Mbps)
Ethernet Port	1 Independent 100Mbps Ethernet Port
PoE	4 ports (IEEE802.3at/af)
Network Function	HTTP, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search(Support Dahua IP camera, DVR, NVS and etc.), Easy4ip
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF 2.4, CGI Conformant
Storage	
Internal HDD	1 SATA III Port, up to 6TB capacity for each HDD
HDD Mode	Single
Auxiliary Interface	
USB	2 ports (1 Rear USB2.0, 1 Front USB2.0)
Electrical	
Power Supply	Single, DC48V/1.25A
Power Consumption	<4W (without HDD)
Working Environment	Operating: -10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa Storage: -20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH
Dimension (W× D× H)	Compact 1U, 260mm×224.9mm×47.6mm (10.2" x 8.9" x 1.9")
Weight	0.8kg (1.76 lb) (without HDD)