

# ELI-QUHD-DVR32: Specifications

## 32ch Sibell Quadbrid DVR 8HDD TVI/AHD/Analog



### Key Features:

- 32ch TVI / AHD 2.0 video input
- 32ch 1080P / 1080P lite / 720P recording
- 32ch DVR: 1ch IP 3MP / 1080P / 960H / 720P recording
- H.264 high profile compression format
- Intuitive, user-friendly GUI with Modular Design
- Recording Modes in Manual, motion, sensor or timer
- Search video: by time, calendar and events
- Express backup options
- Remote Monitoring via Browser or CMS
- Mobile Viewing Via Sibell Mobile App on IOS & Android
- NAT function & QRCode scan to set up mobile viewing

Model#: ELI-QUHD-DVR32		
System	Compression	Standard H.264 High Profile
	CPU	Cortex A9
	OS	Embedded Linux
Video	Input	BNC × 32 Support TVI 1080P@25 / 30fps, 720P@25 / 30 / 50 / 60fps and AHD 1080P@25 / 30fps, 720P@25 / 30fps, WD1 input
	Output	HDMI x1: 1920 × 1080 / VGA × 1: 1920 × 1080
Audio	Input	RCA × 16
	Output	RCA × 1
	2-way audio	RCA × 1
Record	Resolution	1080P: 1920 × 1080, 720P:1280 × 720, WD1
	Frame Rate	1080P: 400 fps ( PAL ) / 480 fps ( NTSC )
		720p: 800 fps ( PAL ) / 960 fps ( NTSC )
	Bit rate	768Kbps ~ 8Mbps
	Encode	VBR / CBR
	Quality	6 Level
	Mode	Manual, timer, motion, sensor
File manager	Lock, unlock	
Playback	Playback	8 CH
	Search	Time / calendar search, event ( motion, external alarm )
	Smart Search	Highlighted date and time to display the channel record
	Function	Play, pause, FF, FB, digital zoom
Alarm	Mode	Sensor, motion, video loss
	Input	16 CH
	Output	4 CH
	Triggering	Record, PTZ move, alarm out, e-mail, etc
Network	Interface	RJ45 10M / 100M / 1000M × 1
	Protocal	TCP / IP, UDP, DHCP, DNS, PPPoE, DDNS
	Others	Up to 10 online users , dual stream
Mobile Device	OS	iPhone, Andriod   Function: Multi-screen surveillance ( for certain model ) , record, snapshot, PTZ control, save the device list
I / O	HDD	SATA × 8, e-SATA × 1
	RS485	RS485 × 2, one for PTZ, another for keyboard
	USB	USB 2.0 × 2, one for mouse, another for USB backup device
	IR controller	Yes
Others	Power supply	DC12V
	Consumption	< 26W ( without HDD )
	Dimensions ( mm )	430 × 450 × 90 ( W × D × H )
	Work Environment	-10 °C ~ 50 °C 10% ~ 90% humidity