

# ELI-IP5-ED4-28R

## 4MP EYEBALL DOME WITH IR

### Key Features: ELI-IP5-ED4-28R

- Up to 4MP (2688X1520) Resolution
- 2.8mm Fixed Lens
- 1/3" 4Megapixel progressive scan CMOS
- H.264+ & H.264 dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- IR LEDs Max length 98 feet (30 meters)
- IP67, PoE
- Remote Monitoring: Web Browser, IOS, & Android

\*Specifications are subject to change without Notice.



### High Resolution ULTRA HD

High Definition Resolutions settings up to 4MP



### HIGH POWERED IR LEDs

Equipped with high powered IR LED's for night vision views up to 98 feet (30 meters)



# ELI-IP5-ED4-28R

## 4MP EYEBALL DOME WITH IR

<b>Model Number</b>	ELI-IP5-ED4-28R
Image Sensor	1/3" 4Megapixel progressive scan CMOS
Effective Pixels	2688(H) x1520(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3(4)s~1/100000s
Min. Illumination	0. 1Lux/F2.0(Color), 0Lux/F2.0(IR on)
S/N Ratio	More than 50dB
<b>Camera Features</b>	
Max. IR LEDs Length	up to 98 feet (30 meters)
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
<b>Lens</b>	
Focal Length	2.8mm
Max Aperture	F2.0
Angle of View	H: 106°
Mount Type	Board-in Type
<b>Video</b>	
Compression	H.264+ / H.264
Resolution	4M(2688x1520)/3M(2304x1296)/1080P(1920x1080)/720P(1280x720)/ D1(704x576/704x480) / CIF(352x288/352x240)
Frame Rate	Main Stream: 4M(1 ~ 20fps)/3M(1 ~ 25/30fps) Sub Stream: D1 (1 ~ 25/30fps)
Bit Rate	H.264: 32kbps~8192kbps
Corridor Mode	Support

<b>Audio</b>	
Compression	N/A
Interface	N/A
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Wi-Fi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
Compatibility	ONVIF, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
<b>Auxiliary Interface</b>	
Memory Slot	N/A
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A
<b>General</b>	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	<4.7W(IR on)
Working Environment	-30°C~+60°C, Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	N/A
Dimensions	Φ4.25in×3.30in (Φ108mm×84mm)
Weight	0.55lbs/0.25Kg(with package 0.83lbs/0.38 Kg)